

HYT

TC320

Business Analog Portable Radio

Unique for its compact and professional design, as well as its superb sound quality. Its strong casing prevents damage against drops of up to 5ft. This radio enables businesses to enjoy dependable communications at an extremely low cost.



Highlights

- **Wide Communication Range**
2W output power has a range of up to 6 miles.
- **Durable Casing**
Compact durable design that can withstand a 1.5 meter drop.
- **Long Battery Life**
1700mAh high capacity Li-Ion battery lasts approximately 12hrs.
- **User Friendly Design**
With its ergonomic design, this slim and compact radio can enhance user comfort, while maintaining a professional and fashionable appearance.
- **Double Injection Molding**
The combination of double injection molding and grip technology brings users a comfortable and convenient operation experience.
- **Mini-USB Interface**
Chargeable and Programmable through the Mini-USB port, plug directly into an outlet or the optional charger.

Features

- Audio Compressor
- Scrambler compatible w/ TC320 UHF2 & TC518
- VOX Earpiece
- Battery Strength Indicator
- High / Low Power Switchable
- Programmable 25 / 12.5 KHz Channel Spacing
- Monitor
- CTCSS / CDCSS and Squelch Tail Elimination
- Channel Scan
- Auto Battery Save
- Low Battery Alert
- Busy Channel Lockout (BCL)
- Time-out-timer (TOT)
- PC Programmable
- Wired Clone

Applications

Retail



Hotel



Restaurants



Education

Hospital

Business

Property Management



Accessories

Included

- Li-Ion Battery
- Power Supply
- Antenna
- Belt Clip
- Neck Strap

Optional



Ear set with In-Line MIC EHS12-A



Rapid-rate Charger (for Li-Ion Battery) CH05L01



Programming Cable (USB Port) PC30



6-Unit Switching Power (Combine w/ CH05L01) PS4001

See website for full list

Specifications

| | | |
|--------------------|----------------------------------|---------------------------|
| General | Frequency Range | UHF1: 400 - 470MHz |
| | Channel Capacity | 16 |
| | Channel Spacing | 25 / 12.5KHz |
| | PLL Channel Stepping | 5 kHz, 6.25 kHz |
| | Operating Voltage | 3.7V (rated) |
| | RF Power Output | 2W |
| | Battery | 1700mAh (Li-Ion) |
| | Battery Life (5-5-90 Duty Cycle) | Approx. 10hrs |
| | Frequency Stability | ±0.5ppm |
| | Operating Temperature | -4° F ~ 131° F |
| | Antenna Impedance | 50 Ω |
| | Dimensions (HxWxD) | 3.94 x 1.89 x 1.06 Inches |
| | Weight | 4.76oz |
| | FCC ID | See website for full list |
| Canada Industry ID | See website for full list | |



Hytera_TC-320_DS-vC

HYT, Hytera are registered trademarks of Hytera Communications Co., Ltd.

© 2025 Hytera Communications Co., Ltd. All Rights Reserved.

Hytera retains right to change the product design and specification.



Hytera
US Inc

Hytera US Inc.

8 Whatney, Suite 200, Irvine, CA 92618

(954) 846-1011

1363 Shotgun Road, Sunrise, FL 33326

(954) 846-1011

www.hytera.us

info@hytera.us